

# Holbrook Sandfaced Brown



**Ibstock**  
At the heart of building



## Product Information

|                        |                                    |
|------------------------|------------------------------------|
| Ibstock Code:          | 4119                               |
| Type:                  | Wirecut                            |
| Facing Description:    | Sandfaced                          |
| Dry Brick Weight (kg): | 2.1kg                              |
| Pack Quantity:         | 500                                |
| Packaging (standard):  | Banded (plastic) And Shrinkwrapped |
| Factory:               | South Holmwood                     |

## Technical Specification (to BS EN 771-1)

|   |                       |
|---|-----------------------|
| Brick Dimensions (L x W x H mm):                                    | 215x102x65            |
| Size Tolerances Mean & Range:                                       | T2 R1                 |
| Configuration:  | Vertically Perforated |
| Voids (%):  | 30-34                 |
| Compressive Strength (N/mm <sup>2</sup> ):                          | 40                    |
| Active Soluble Salts:   | S2                    |
| Water Absorption (% weight):  | 12                    |
| Durability:   | F2                    |
| Gross Dry Density (Sound Insulation) (Kg/m <sup>3</sup> ):          | 1450                  |
| Equivalent Thermal Conductivity "K" value 5% Exposed:               | Refer to Ibstock      |
| Initial Rate of Absorption (Suction Rate) (Kg/m <sup>2</sup> /min): | Refer to Ibstock      |
| EAN:  | 5036335025611         |